Atty. Dkt No 32405R096 **PATENT** 

#### IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicants:

TADASHI MASUDA

Serial No.:

New

Group Art Unit: To Be Assigned

Filed:

December 28, 2001

Examiner: To Be Assigned

For

WIPER ASSEMBLY FOR VEHICLE

### PRELIMINARY AMENDMENT

Commissioner for Patents Washington, D.C. 20231

Sir:

Prior to or concurrent with calculation of the filing fees, please amend this application as follows.

#### **IN THE CLAIMS:**

Applicant has attached to this Amendment documents entitled "Marked-up Copy of the Previous Claims" and "Amended Claims". Please replace present claim 4 in this application with amended claim 4 shown in the document entitled "Amended Claims". Please add new claims 5-6 as shown in the document entitled "Amended Claims".

## **REMARKS**

Entry and consideration of this Preliminary Amendment are respectfully requested prior to or concurrent with calculation of the filing fees. This Preliminary Amendment is being filed to remove the multiple dependent claims to avoid the surcharge.

		• .		• . 1
Examination	on the	mente	10	awaited.
Examination	on the	THOTHS.	10	awanca.

Respectfully submitted,

SMITH, GAMBRELL & RUSSELL, LLP

By:\_

Dennis C. Rodgers, Reg. No.32,936 1850 M Street, N.W., Suite 800

Washington, D.C. 20036 Telephone: (202) 263-4300 Facsimile: (202) 263-4329

December 28, 2001

MARKED UP COPY OF THE PREVIOUS CLAIM

4. The vehicle wiper assembly of [any one of claim 1 to claim 3] <u>claim 1</u>, wherein each of said first weak point and said second weak point having low rupture strength is provided in the vicinity of a vehicle fixing section of a pivot holder for rotatably supporting a pivot shaft for attaching a base end section of the wiper arm.

# AMENDED CLAIMS

- 4. The vehicle wiper assembly of claim 1, wherein each of said first weak point and said second weak point having low rupture strength is provided in the vicinity of a vehicle fixing section of a pivot holder for rotatably supporting a pivot shaft for attaching a base end section of the wiper arm.
- 5. (New) The vehicle wiper assembly of claim 2, wherein each of said first weak point and said second weak point having low rupture strength is provided in the vicinity of a vehicle fixing section of a pivot holder for rotatably supporting a pivot shaft for attaching a base end section of the wiper arm.
- 6. (New) The vehicle wiper assembly of claim 3, wherein each of said first weak point and said second weak point having low rupture strength is provided in the vicinity of a vehicle fixing section of a pivot holder for rotatably supporting a pivot shaft for attaching a base end section of the wiper arm.